

Toluene (0.001% - 0.099%), Oxygen (19.5% - 23.5%) in balance Nitrogen

Safety Data Sheet 50053

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 04/01/2015

Revision date: 12/12/2017

Supersedes: 04/01/2015

Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form : Mixtures
 Product name : Toluene (0.001% - 0.099%), Oxygen (19.5% - 23.5%) in balance Nitrogen

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Test gas/Calibration gas.

1.3. Supplier

Calgaz, division of Airgas USA LLC
 821 Chesapeake Drive
 Cambridge, 21613 - USA
 T 1-410-228-6400 - F 1-410-228-4251
info@Calgaz.com - www.Calgaz.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300
 Internationally: 1-703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Gases under pressure H280 Contains gas under pressure; may explode if heated
 Compressed gas

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS04

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H280 - Contains gas under pressure; may explode if heated
 OSHA-H01 - May displace oxygen and cause rapid suffocation
 CGA-HG24 - Supports combustion

Precautionary statements (GHS-US) :

P202 - Do not handle until all safety precautions have been read and understood.
 P271 - Use only outdoors or in a well-ventilated area.
 P280 - Wear eye protection, face protection, protective gloves, protective clothing.
 P403 - Store in a well-ventilated place.
 P501 - Dispose of contents/container in accordance with local/regional/national/international regulations
 CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C/125 °F
 CGA-PG05 - Use a back flow preventive device in the piping
 CGA-PG06 - Close valve after each use and when empty
 CGA-PG10 - Use only with equipment rated for cylinder pressure
 CGA-PG14 - Approach suspected leak area with caution
 CGA-PG21 - Open valve slowly

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Toluene (0.001% - 0.099%), Oxygen (19.5% - 23.5%) in balance Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Nitrogen	(CAS-No.) 7727-37-9	76.401 - 80.499	Press. Gas (Comp.), H280
Oxygen	(CAS-No.) 7782-44-7	19.5 - 23.5	Ox. Gas 1, H270 Press. Gas (Comp.), H280
Toluene	(CAS-No.) 108-88-3	0.001 - 0.099	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:gas), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Adverse effects not expected from this product.
First-aid measures after skin contact : Adverse effects not expected from this product.
First-aid measures after eye contact : Adverse effects not expected from this product.
First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : May displace oxygen and cause rapid suffocation. Adverse effects not expected from this product.
Symptoms/effects after skin contact : Adverse effects not expected from this product.
Symptoms/effects after eye contact : Adverse effects not expected from this product.
Symptoms/effects after ingestion : Ingestion is not considered a potential route of exposure.
Symptoms/effects upon intravenous administration : Not known.
Chronic symptoms : Adverse effects not expected from this product.

4.3. Immediate medical attention and special treatment, if necessary

If you feel unwell, seek medical advice. If breathing is difficult, give oxygen.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Specific hazards arising from the chemical

Fire hazard : The product is not flammable.
Explosion hazard : Product is not explosive. Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.
Reactivity : None known.
Hazardous combustion products : None

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire.
Protection during firefighting : Standard protective clothing and equipment (e.g. Self Contained Breathing Apparatus) for fire fighters. Do not enter fire area without proper protective equipment, including respiratory protection.
Specific methods : Exposure to fire may cause containers to rupture/explode. Continue water spray from protected position until container stays cool. Move containers away from the fire area if this can be done without risk.

Toluene (0.001% - 0.099%), Oxygen (19.5% - 23.5%) in balance Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Ensure adequate ventilation.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment consistent with the site emergency plan.
Emergency procedures : Evacuate personnel to a safe area. Close doors and windows of adjacent premises. Keep containers closed. Mark the danger area. Seal off low-lying areas. Keep upwind.

6.1.2. For emergency responders

Protective equipment : Standard protective clothing and equipment (e.g. Self Contained Breathing Apparatus) for fire fighters. Equip cleanup crew with proper protection.
Emergency procedures : Evacuate and limit access. Ventilate area.

6.2. Environmental precautions

Try to stop release if without risk.

6.3. Methods and material for containment and cleaning up

For containment : Try to stop release if without risk.
Methods for cleaning up : Dispose of contents/container in accordance with local/regional/national/international regulations.

6.4. Reference to other sections

See also Sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use. Use only with equipment rated for cylinder pressure. Close valve after each use and when empty.
Precautions for safe handling : Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area.
Safe handling of the gas receptacle : Protect cylinders from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.
Safe use of the product : The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularly) checked for leaks before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Comply with applicable regulations.
Storage conditions : Do not expose to temperatures exceeding 52 °C/ 125 °F. Keep container closed when not in use. Protect cylinders from physical damage; do not drag, roll, slide or drop. Store in well ventilated area.
Incompatible products : None known.
Incompatible materials : Flammable materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Toluene (108-88-3)		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
OSHA	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	500 ppm Peak (10 minutes)
IDLH	US IDLH (ppm)	500 ppm

Toluene (0.001% - 0.099%), Oxygen (19.5% - 23.5%) in balance Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Toluene (108-88-3)		
NIOSH	NIOSH REL (TWA) (mg/m ³)	375 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	560 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
Oxygen (7782-44-7)		
Not applicable		
Nitrogen (7727-37-9)		
Not applicable		

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure exposure is below occupational exposure limits (where available). Provide adequate general and local exhaust ventilation. Systems under pressure should be regularly checked for leakages. Consider the use of a work permit system e.g. for maintenance activities.
- Environmental exposure controls : Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear working gloves when handling gas containers. 29 CFR 1910.138: Hand protection

Eye protection:

Wear safety glasses with side shields. 29 CFR 1910.133: Eye and Face Protection

Skin and body protection:

Wear suitable protective clothing, e.g. lab coats, coveralls or flame resistant clothing.

Respiratory protection:

None necessary during normal and routine operations. See Sections 5 & 6.

Thermal hazard protection:

None necessary during normal and routine operations.

Other information:

Wear safety shoes while handling containers. 29 CFR 1910.136: Foot Protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Clear, colorless gas.
Color	: Colorless
Odor	: Odorless
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available

Toluene (0.001% - 0.099%), Oxygen (19.5% - 23.5%) in balance Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Relative gas density	: Similar to air
Solubility	: Water: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: Not applicable (non-flammable gas).
Oxidizing properties	: Supports combustion.

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

None known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Can form explosive mixtures with flammable materials.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Flammable materials.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure	: Inhalation
Acute toxicity	: Not classified

Toluene (108-88-3)	
LD50 oral rat	5580 mg/kg Sig Ald
LD50 dermal rabbit	12196 mg/kg Sig Ald
LC50 inhalation rat (ppm)	13001 ppm/4h AS400
ATE US (oral)	5580.000 mg/kg body weight
ATE US (dermal)	12196.000 mg/kg body weight
ATE US (gases)	13001.000 ppmV/4h
ATE US (vapors)	48.990 mg/l/4h
Oxygen (7782-44-7)	
LC50 inhalation rat (ppm)	800000 ppm/4h
ATE US (gases)	800000.000 ppmV/4h
Nitrogen (7727-37-9)	
LC50 inhalation rat (ppm)	820000 ppm/4h
ATE US (gases)	820000.000 ppmV/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified

Toluene (0.001% - 0.099%), Oxygen (19.5% - 23.5%) in balance Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified

Specific target organ toxicity – repeated exposure	: Not classified
--	------------------

Aspiration hazard	: Not classified
-------------------	------------------

Symptoms/effects after inhalation	: May displace oxygen and cause rapid suffocation. Adverse effects not expected from this product.
-----------------------------------	--

Symptoms/effects after skin contact	: Adverse effects not expected from this product.
-------------------------------------	---

Symptoms/effects after eye contact	: Adverse effects not expected from this product.
------------------------------------	---

Symptoms/effects after ingestion	: Ingestion is not considered a potential route of exposure.
----------------------------------	--

Symptoms/effects upon intravenous administration	: Not known.
--	--------------

Chronic symptoms	: Adverse effects not expected from this product.
------------------	---

SECTION 12: Ecological information

12.1. Toxicity

Toluene (108-88-3)	
LC50 fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

Oxygen (7782-44-7)	
Persistence and degradability	No ecological damage caused by this product.

Nitrogen (7727-37-9)	
Persistence and degradability	No ecological damage caused by this product.

12.3. Bioaccumulative potential

Toluene (108-88-3)	
Log Pow	2.7

Oxygen (7782-44-7)	
Log Pow	Not applicable for inorganic gases.
Bioaccumulative potential	No ecological damage caused by this product.

Nitrogen (7727-37-9)	
Log Pow	Not applicable for inorganic gases.
Bioaccumulative potential	No ecological damage caused by this product.

12.4. Mobility in soil

Oxygen (7782-44-7)	
Ecology - soil	No ecological damage caused by this product.

Nitrogen (7727-37-9)	
Ecology - soil	No ecological damage caused by this product.

Toluene (0.001% - 0.099%), Oxygen (19.5% - 23.5%) in balance Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.5. Other adverse effects

Effect on ozone layer	: No known effects from this product.
Effect on global warming	: No known effects from this product.
GWPMix comment	: No known effects from this product.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Contact supplier if guidance is required. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded.
Product/Packaging disposal recommendations	: Refer to the CGA Pamphlet P-63 "Disposal of Gases" available at www.cganet.com for more guidance on suitable disposal methods.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN1956 Compressed gas, n.o.s., 2.2
UN-No.(DOT)	: UN1956
Proper Shipping Name (DOT)	: Compressed gas, n.o.s.
Class (DOT)	: 2.2 - Class 2.2 - Non-flammable compressed gas 49 CFR 173.115
Hazard labels (DOT)	: 2.2 - Non-flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 302;305
DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315
DOT Symbols	: G - Identifies PSN requiring a technical name
DOT Packaging Exceptions (49 CFR 173.xxx)	: 306;307
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 150 kg
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
Other information	: No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

Transport document description (IMDG)	: UN 1956 Compressed gas, n.o.s., 2
UN-No. (IMDG)	: 1956
Proper Shipping Name (IMDG)	: Compressed gas, n.o.s.
Class (IMDG)	: 2 - Gases
Limited quantities (IMDG)	: 120 ml

Air transport

Transport document description (IATA)	: UN 1956 Compressed gas, n.o.s., 2.2
UN-No. (IATA)	: 1956
Proper Shipping Name (IATA)	: Compressed gas, n.o.s.
Class (IATA)	: 2

Toluene (0.001% - 0.099%), Oxygen (19.5% - 23.5%) in balance Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

Toluene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ	1000 lb
-----------	---------

SARA Section 313 - Emission Reporting	1 %
---------------------------------------	-----

Oxygen (7782-44-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Nitrogen (7727-37-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Toluene (108-88-3)

Listed on the Canadian DSL (Domestic Substances List)

Oxygen (7782-44-7)

Listed on the Canadian DSL (Domestic Substances List)

Nitrogen (7727-37-9)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Toluene (108-88-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Oxygen (7782-44-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Nitrogen (7727-37-9)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Toluene (108-88-3)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Poisonous and Deleterious Substances Control Law
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

Oxygen (7782-44-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

Toluene (0.001% - 0.099%), Oxygen (19.5% - 23.5%) in balance Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Nitrogen (7727-37-9)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

Toluene (108-88-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
No	Yes	No	No	

Toluene (108-88-3)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

Oxygen (7782-44-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Nitrogen (7727-37-9)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 12/12/2017
Other information : This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this product.

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H270	May cause or intensify fire; oxidizer
H280	Contains gas under pressure; may explode if heated
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure

Toluene (0.001% - 0.099%), Oxygen (19.5% - 23.5%) in balance Nitrogen

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR, 1910.1200. Other government regulations must be reviewed for applicability to this gas mixture. To the best of Calgaz's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either express or implied, are provided. The information contained herein relates only to this specific product. If this gas mixture is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.